1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

: Shell Sirius X 40 **Material Name**

Recommended Use / **Restrictions of Use**

Engine oil.

Product Code : 001A9054

Supplier : PT Shell Indonesia

Talavera Office Park 22nd-27th Floor

22-26 Jl. Letjen TB Simatupang Kav.

Jakarta Selatan 12430

Indonesia

: (+62) 2175924700 **Telephone** Fax (+62) 2175924679 **Emergency Telephone** (+62) 811 984 290

Number

: If you have any enquiries about the content of this MSDS

please email lubricantSDS@shell.com

2. HAZARDS IDENTIFICATION

Email Contact for MSDS

GHS Classification : NOT HAZARDOUS, Category

GHS Label Elements

Symbol(s)

No symbol

Signal Words No signal word

GHS Hazard Statements PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS:

Not classified as a health hazard under GHS criteria.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

GHS Precautionary

Statements

PREVENTION:

No precautionary phrases.

RESPONSE:

No precautionary phrases.

STORAGE:

No precautionary phrases.

DISPOSAL:

No precautionary phrases.

Other Hazards which do

not result in Classification

: Not classified as flammable but will burn.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Preparation description: Highly refined mineral oils and additives.

Hazardous Components

Chemical IdentityCASIdentification No.Conc.Calcium long chain alkyl salicylate1.00 - 5.00 %Zinc alkaryl dithiophosphate98073-07-5308-565-81.00 - 3.00 %

Additional Information : The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346. Refer to chapter 16 for full text of

EC R-phrases.

The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

4. FIRST AID MEASURES

General Information : Not expected to be a health hazard when used under normal

conditions.

Inhalation : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

Skin Contact: Remove contaminated clothing. Flush exposed area with water

and follow by washing with soap if available. If persistent

irritation occurs, obtain medical attention.

Eye Contact : Flush eye with copious quantities of water. If persistent

irritation occurs, obtain medical attention.

Ingestion : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Most Important

Symptoms/Effects, Acute

& Delayed

Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.

Ingestion may result in nausea, vomiting and/or diarrhoea.

Immediate medical attention, special

treatment

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific hazards arising

from Chemicals

: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic

compounds.

Suitable Extinguishing

Media

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable Extinguishing

Media

Protective Equipment & Precautions for Fire

Fighters

: Do not use water in a jet.

: Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations.

Personal Precautions, Protective Equipment and Emergency Procedures

Environmental Precautions

: Avoid contact with skin and eyes.

: Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate

Methods and Material for Containment and Clean

Up

Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

: Local authorities should be advised if significant spillages

cannot be contained.

7. HANDLING AND STORAGE

Additional Advice

General Precautions Use local exhaust ventilation if there is risk of inhalation of

> vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Precautions for Safe Handling

Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment

should be used.

Conditions for Safe

Storage

Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage Temperature: 0 - 50 °C / 32 - 122 °F

Recommended Materials For containers or container linings, use mild steel or high

density polyethylene.

Unsuitable Materials

Other Advice

PVC.

Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

MSDS_ID Print Date 16.03.2010

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

| Material | Source | Туре | ppm | mg/m3 | Notation |
|-------------------|--------|---------|-----|----------|----------|
| Oil mist, mineral | ACGIH | TWA | | 5 mg/m3 | |
| | | [Mist.] | | | |
| | ACGIH | STEL | | 10 mg/m3 | |
| | | [Mist.] | | | |
| | ID OEL | NAB | | 5 mg/m3 | |
| | | [Mist.] | | | |

Biological Exposure Index (BEI) - See reference for full details

Data not available

Appropriate Engineering Controls

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne

concentrations to be generated.

Individual Protection Measures : Personal protective equipment (PPE) should meet

recommended national standards. Check with PPE suppliers.

Respiratory Protection

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65°C(149°F)].

Hand Protection

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

Application of a non-perfumed moisturizer is recommended.

Eye Protection : Wear safety glasses or full face shield if splashes are likely to

occur.

Protective Clothing : Skin protection not ordinarily required beyond standard issue

work clothes.

Thermal Hazards

Monitoring Methods : Monitoring of the concentration of substances in the breathing

zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also

be appropriate.

Environmental Exposure

Controls

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber. Liquid at room temperature.

Odour : Slight hydrocarbon
Odour threshold : Data not available
pH : Not applicable.

Initial Boiling Point and : > 280 °C / 536 °F estimated value(s)

Boiling Range

Pour point : Typical -18 °C / 0 °F

Flash point : Typical 230 °C / 446 °F (COC)

Lower / upper : Typical 1 - 10 %(V) (based on mineral oil)

Flammability or

Explosion limits

Auto-ignition temperature : > 320 °C / 608 °F

Vapour pressure : < 0.5 Pa at 20 °C / 68 °F (estimated value(s))

Relative Density

Density : Typical 890 kg/m3 at 15 °C / 59 °F

Water solubility : Negligible.

Solubility in other : Data not available

solvents

n-octanol/water partition

coefficient (log Pow)

: > 6 (based on information on similar products)

Dynamic viscosity : Data not available

Kinematic viscosity : Typical 139 mm2/s at 40 °C / 104 °F

Vapour density (air=1) : > 1 (estimated value(s))
Evaporation rate : Data not available

(nBuAc=1)

Decomposition : Data not available

Temperature

Flammability : Data not available

10. STABILITY AND REACTIVITY

Chemical Stability : Stable.

Possibility of Hazardous : Data not available

Reactions

Conditions to Avoid : Extremes of temperature and direct sunlight.

Incompatible Materials : Strong oxidising agents.

Hazardous

: Hazardous decomposition products are not expected to form

Decomposition Products

during normal storage.

11. TOXICOLOGICAL INFORMATION

Basis for Assessment : Information given is based on data on the components and the

toxicology of similar products.

Likely Routes of

Exposure

Acute Oral Toxicity

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
 Expected to be of low toxicity: LD50 > 5000 mg/kg, Rat

Acute Dermal Toxicity : Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit

Acute Inhalation Toxicity : Not considered to be an inhalation hazard under normal

conditions of use.

Skin Corrosion/Irritation: Expected to be slightly irritating. Prolonged or repeated skin

contact without proper cleaning can clog the pores of the skin

resulting in disorders such as oil acne/folliculitis.

Serious Eye Damage/Irritation Respiratory Irritation

: Expected to be slightly irritating.

: Inhalation of vapours or mists may cause irritation.

Respiratory or Skin

Sensitisation

Repeated Dose Toxicity

Not expected to be a skin sensitiser.

Not expected to be a hazard.

Aspiration Hazard : Not considered an aspiration hazard.

Germ Cell Mutagenicity: Not considered a mutagenic hazard.

Carcinogenicity : Product contains mineral oils of types shown to be non-

carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic

effects.

Reproductive and Developmental Toxicity Additional Information

: Not expected to be a hazard.

: Used oils may contain harmful impurities that have

accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible. Continuous contact with used engine oils has caused skin

cancer in animal tests.

12. ECOLOGICAL INFORMATION

Basis for Assessment : Ecotoxicological data have not been determined specifically for

this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity : Poorly soluble mixture. May cause physical fouling of aquatic

organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

Microorganisms

Mobility

Data not available

: Liquid under most environmental conditions. Floats on water. If

it enters soil, it will adsorb to soil particles and will not be

mobile.

Persistence/degradability : Expected to be not readily biodegradable. Major constituents

are expected to be inherently biodegradable, but the product contains components that may persist in the environment.Contains components with the potential to bioaccumulate.

Bioaccumulative

Potential

Other Adverse Effects

Product is a mixture of non-volatile components, which are not

expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical

ozone creation potential or global warming potential.

13. DISPOSAL CONSIDERATIONS

Material Disposal : Recover or recycle if possible. It is the responsibility of the

waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in

drains or in water courses.

Container Disposal : Dispose in accordance with prevailing regulations, preferably to

a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Local Legislation : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated

This material is not classified as dangerous under ADR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EINECS : All components

listed or polymer

exempt.

TSCA : All components

listed.

16. OTHER INFORMATION

MSDS Version Number : 1.1

MSDS Effective Date : 15.03.2010

MSDS Revisions : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

MSDS Distribution : The information in this document should be made available to

all who may handle the product.

Disclaimer : This information is based on our current knowledge and is

intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property

of the product.